

The VT4-DWS inactivates the following microorganisms: Cryptosporidium, Giardia, E.Coli and Fecal Coliform. Treat your drinking water with the point-of-use, single tap VT4-DWS. The compact system offers additional pre-filtration for a more complete solution, with flow rates up to 3.5 gpm (13 lpm).

Applications:

- Home
- Hotel Hospitality
- Small Business



Pre-Filter Solution

Includes two 20" filter housing with 5 micron sediment and taste/odour/lead removal cartridges.

Convenient

Mounted on a heavy-duty, painted steel bracket for ease of installation

Reliable

High-performance UV lamp, rigorously tested to provide consistent output over the entire lamp life (9000 hours)

The power supply features and LED power and lamp on

Perfect for a wide range of single-faucet, point-of-use or low flow point-of-entry water treatment solutions in homes, cottages, or OEM applications.

Table 1

Connection Size	3/8" FNPT/TUBE
Dimensions	19" x 27 1/2" x 6" (48 cm x 70 cm x 15 cm)
Flow Rate	16mJ/cm2: 6.5 GPM / 24 LPM
	30mJ/cm2: 3.5 GPM / 13 LPM
	40mJ/cm2: 2.5 GPM / 9 LPM
Parameters Treated	Chlorine, Lead, Turbidity/Cloudiness
Power Consumption	20 watts
Shipping weight	20 Lbs.